

**U.S. Serial No. 10/689,537**  
**Response to Office Action dated January 9, 2006**

In the Claims:

Please amend Claim 1, as follows:

Claim 1 (Currently Amended): A portable terminal device of the foldable type comprising a pair of flat cabinets openably connected to each other by a hinge mechanism, each of the cabinets comprising a front cabinet half segment to be opposed to the other cabinet when closed and a rear cabinet half segment joined to the front cabinet half segment, said front cabinet half segment being a separate piece from said rear cabinet half segment, one of the pair of cabinets having the front cabinet half segment thereof connected at an end portion thereof to the hinge mechanism and having the rear cabinet half segment thereof engaged with the front cabinet half segment thereof, the other cabinet having the rear cabinet half segment thereof connected at an end portion thereof to the hinge mechanism and having the front cabinet half segment thereof engaged with the rear cabinet half segment thereof,

such that when the pair of cabinets are closed, with extraneous matter therebetween, no clearance is created in the joint between the front cabinet half segment and rear cabinet half segment of either of the pair of cabinets.

Claim 2 (Original): A portable terminal device of the foldable type according to claim 1 wherein one of the pair of flat cabinets is a manipulation-side cabinet provided with a plurality of manual keys, and the other cabinet is a display-side cabinet provided with a display, the front cabinet segment of the manipulation-side cabinet and the rear cabinet segment of the display-side cabinet being connected to each other by the hinge mechanism.

Claim 3 (Original): A portable terminal device of the foldable type according to claim 1 wherein the front cabinet segment of the manipulation-side cabinet is provided with a pair of annular pieces projecting from one end thereof and spaced apart from each other, and the rear cabinet segment of the display-side cabinet is provided with a pair of annular pieces projecting from one end thereof and spaced apart from each other, the annular piece of the manipulation-side cabinet and the annular piece of the display-side cabinet being arranged side by side in contact with each other and have fitted therein a first hinge unit, the other annular piece of the manipulation-side cabinet and the other annular piece of the display-side cabinet being arranged side by side in contact with each other and have fitted therein a second hinge unit.

Claim 4 (Original): A portable terminal device of the foldable type according to claim 3 wherein the front cabinet segment of the manipulation-side cabinet has a circular-arc piece projecting from the end thereof and positioned between the pair of annular pieces, and the rear cabinet segment of the manipulation-side cabinet is provided at one end thereof with a partial member joined to the circular-arc piece for forming a hollow cylinder.

Claim 5 (Original): A portable terminal device of the foldable type according to claim 3 wherein the front cabinet segment of the display-side cabinet is provided with a projecting circular-arc piece positioned between the pair of annular pieces, and the rear cabinet segment of the display-side cabinet

**U.S. Serial No. 10/689,537**  
**Response to Office Action dated January 9, 2006**

is provided at the end thereof with a partial member joined to the circular-arc piece for forming a hollow cylinder.

Claim 6 (Original): A portable terminal device of the foldable type according to claim 4 wherein a circuit board in the manipulation-side cabinet and a display in the display-side cabinet are connected to each other by a flexible lead, and the flexible lead is helically wound inside the hollow cylinders formed by the circular-arc pieces and the partial members.

Claim 7 (Original): A portable terminal device of the foldable type according to claim 5 wherein a circuit board in the manipulation-side cabinet and a display in the display-side cabinet are connected to each other by a flexible lead, and the flexible lead is helically wound inside the hollow cylinders formed by the circular-arc pieces and the partial members.